NSN 6625-00-643-2610

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-643-2610

| Circuit Current For Which Designed: |
|--|
| Dc |
| Dielectric Withstanding Voltage In Volts: |
| 3000.0 |
| Overall Length: |
| 2.060 inches |
| Scale Division Quantity: |
| 50 single indicator single range |
| Overall Diameter: |
| 3.510 inches |
| Mounting Bolt Circle Diameter: |
| 3.160 inches |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Three hole/stud bolt circle |
| Sensitivity Rating: |
| 150.0 millivolts |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.0/+2.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 1.660 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.800 inches |
| Movement Type: |
| Moving iron vane |
| Background Color: |
| White single indicator single range |
| Mounting Facility Type And Quantity: |
| 3 flange |
| Measurement Range: |
| -50.0/+50.0 microamperes, dc single indicator single range |
| Circuit Attachment Method And Quantity: |
| 2 threaded stud |
| Style Designator: |
| Round flush mtg |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 6625-00-643-2610

Ammeter - Page 2 of 2



| _ | | •• | • • | | | | |
|----|----|----|-----|-----|-----|---|----|
| וו | em | ш | 112 | rız | 211 | n | ٠. |
| | | | | | | | |

No

Fiig:

A310a0