

View Online at <https://aerobasegroup.com/nsn/6625-00-643-2757>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

1.780 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.040 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.670 inches

**Overall Height:**

3.940 inches

**Overall Width:**

4.250 inches

**Mounting Stud Length:**

0.500 inches

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Frequency Response Range:**

+0.000 to 400.000 hertz

**Sensitivity Rating:**

80.0 microamperes

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

1.530 inches

**Meter Body Diameter Behind Mounting Flange:**

3.250 inches

**Movement Type:**

Moving iron vane

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 threaded stud

**Scale Graduation Type:**

Nonlinear single indicator single range

**Measurement Range:**

+0.0 to 130.0 volts, ac single indicator single range

**Mounting Stud Diameter:**

0.138 inches

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Material:**

Plastic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0