NSN 6625-00-643-2897

Multiple Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-643-2897

Circuit Current For Which Designed:
Ac or dc
Dielectric Withstanding Voltage In Volts:
1500.0
Overall Length:
3.062 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.344 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.090 inches
Overall Height:
3.750 inches
Overall Width:
4.008 inches
Mounting Stud Length:
0.750 inches
Environmental Protection:
Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and
water resistant
Furnished Items And Quantity:
Nut 6; lockwasher 6; seal 1
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Dial Scale Marking Color:
Black and green and red single indicator all ranges
Accuracy In Percent:
-2.0 to 2.0 at full scale single indicator all ranges
Meter Depth Behind Mounting Flange:
1.491 inches
Meter Body Diameter Behind Mounting Flange:
3.492 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator all ranges
Pointer Color:

External

Power Source:

Black single indicator all ranges

NSN 6625-00-643-2897

Multiple Scale Meter - Page 2 of 2



Mounting Facility Type And Quantity:
4 threaded stud
Scale Graduation Type:
Nonlinear single indicator all ranges
Measurement Range:
+0.0 to 3.0 volts, ac single indicator 2nd range
Mounting Stud Diameter:
0.133 inches
Scale Selection Method:
Terminal
Features Provided:
Zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Special Features:
Ruggedized
Special Markings:
On front, ac-dc-r.F.; volts-dc mils; peak to peak ac volts; dc with multiplier
Material:
Material: Plastic
Plastic
Plastic Nuclear Hardness Critical Feature:
Plastic Nuclear Hardness Critical Feature: Nonhardened
Plastic Nuclear Hardness Critical Feature: Nonhardened Surface Treatment:
Plastic Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint
Plastic Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint Special Test Features:
Plastic Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint Special Test Features: Conforms with mil-m-10304
Plastic Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint Special Test Features: Conforms with mil-m-10304 Style Designator:
Plastic Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint Special Test Features: Conforms with mil-m-10304 Style Designator: Rectangular flush mtg
Plastic Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint Special Test Features: Conforms with mil-m-10304 Style Designator: Rectangular flush mtg Fsc Application Data:
Plastic Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint Special Test Features: Conforms with mil-m-10304 Style Designator: Rectangular flush mtg Fsc Application Data: Test set, elect. Equip.
Plastic Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint Special Test Features: Conforms with mil-m-10304 Style Designator: Rectangular flush mtg Fsc Application Data: Test set, elect. Equip. Shelf Life:
Plastic Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint Special Test Features: Conforms with mil-m-10304 Style Designator: Rectangular flush mtg Fsc Application Data: Test set, elect. Equip. Shelf Life: N/a
Plastic Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint Special Test Features: Conforms with mil-m-10304 Style Designator: Rectangular flush mtg Fsc Application Data: Test set, elect. Equip. Shelf Life: N/a
Plastic Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint Special Test Features: Conforms with mil-m-10304 Style Designator: Rectangular flush mtg Fsc Application Data: Test set, elect. Equip. Shelf Life: N/a Unit Of Measure:
Plastic Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Paint Special Test Features: Conforms with mil-m-10304 Style Designator: Rectangular flush mtg Fsc Application Data: Test set, elect. Equip. Shelf Life: N/a Unit Of Measure: Demilitarization: