NSN 6625-00-643-2956

Ammeter - Page 1 of 2

Ac

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-643-2956

Mounting Hole Diameter:						
Between 0.143 inches and 0.157 inches						
Overall Diameter:						
3.500 inches						
Mounting Bolt Circle Diameter:						
3.160 inches						
Installation Design:						
Panel						
Mounting Arrangement Style:						
Three hole/stud bolt circle						
Frequency Response Range:						
+25.000/+125.000 hertz						
Sensitivity Rating:						
50.0 millivolts						
Dial Scale Marking Color:						
Black single indicator single range						
Accuracy In Percent:						
-2.0/+2.0 at full scale single indicator single range						
Meter Depth Behind Mounting Flange:						
2.390 inches						
Meter Body Diameter Behind Mounting Flange:						
2.800 inches						
Movement Type:						
Moving iron vane						
Moving iron vane Background Color:						
-						
Background Color:						
Background Color: White single indicator single range						
Background Color: White single indicator single range Mounting Facility Type And Quantity:						
Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole						
Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range:						
Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+200.0 amperes, ac single indicator single range						
Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+200.0 amperes, ac single indicator single range Features Provided:						
Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+200.0 amperes, ac single indicator single range Features Provided: Magnetic shield						
Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+200.0 amperes, ac single indicator single range Features Provided: Magnetic shield Circuit Attachment Method And Quantity:						
Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+200.0 amperes, ac single indicator single range Features Provided: Magnetic shield Circuit Attachment Method And Quantity: 2 threaded stud						
Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+200.0 amperes, ac single indicator single range Features Provided: Magnetic shield Circuit Attachment Method And Quantity: 2 threaded stud Material:						
Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+200.0 amperes, ac single indicator single range Features Provided: Magnetic shield Circuit Attachment Method And Quantity: 2 threaded stud Material: Plastic						
Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+200.0 amperes, ac single indicator single range Features Provided: Magnetic shield Circuit Attachment Method And Quantity: 2 threaded stud Material: Plastic Style Designator:						

NSN 6625-00-643-2956

Ammeter - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0