

View Online at <https://aerobasegroup.com/nsn/6625-00-643-3146>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

2.330 inches

**Mounting Hole Diameter:**

0.125 inches

**Scale Division Quantity:**

31 single indicator single range

**Overall Diameter:**

2.695 inches

**Environmental Protection:**

Shock resistant and vibration resistant

**Mounting Bolt Circle Diameter:**

2.440 inches

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-5.0 to 5.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

1.600 inches

**Meter Body Diameter Behind Mounting Flange:**

2.210 inches

**Movement Type:**

Moving iron vane

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

-10.0 to 20.0 decibels single indicator single range

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

Ruggedized

**Special Markings:**

1.9 v below 0 point on scale; rectifier type; zero power level; 6 milliwatts 600 ohms

**Material:**

Aluminum and steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Enamel

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A310a0