

View Online at <https://aerobasegroup.com/nsn/6625-00-643-3224>

Circuit Current For Which Designed:

Dc

Overall Length:

3.469 inches

Mounting Hole Diameter:

Between 0.147 inches and 0.155 inches

Scale Division Quantity:

10 single indicator single range

Overall Diameter:

3.500 inches

Environmental Protection:

Shock resistant and vibration resistant

Mounting Bolt Circle Diameter:

Between 3.154 inches and 3.166 inches

End Application:

Nimitz class cvn, forrestal class cv, deep submergence systems programs (dssp), shipboard material handling equipment (mhe), recovery vehicle, full tracked medium, w/e (m88a1), an/tps-73 usmc airport surveillance radar and beacon set, shop equipment, contact maintenance, truck mounted, central office, telephone auto.

Indicator Type:

Vibrating reed

Installation Design:

Panel

Register Quantity:

1

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator single range

Resonant Reed Quantity:

11

Meter Depth Behind Mounting Flange:

2.688 inches

Meter Body Diameter Behind Mounting Flange:

2.680 inches

Movement Type:

Vibrating reed

Background Color:

White single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+55.0 to 65.0 hertz single indicator single range

Criticality Code Justification:

Feat

Circuit Attachment Method And Quantity:

2 solder lug

Special Features:

Nuclear hardness critical hardness feature - nonhardened.

Material:

Steel

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0