

View Online at <https://aerobasegroup.com/nsn/6625-00-643-3224>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

3.469 inches

**Mounting Hole Diameter:**

Between 0.147 inches and 0.155 inches

**Scale Division Quantity:**

10 single indicator single range

**Overall Diameter:**

3.500 inches

**Environmental Protection:**

Shock resistant and vibration resistant

**Mounting Bolt Circle Diameter:**

Between 3.154 inches and 3.166 inches

**End Application:**

Nimitz class cvn, forrestal class cv, deep submergence systems programs (dssp), shipboard material handling equipment (mhe), recovery vehicle, full tracked medium, w/e (m88a1), an/tps-73 usmc airport surveillance radar and beacon set, shop equipment, contact maintenance, truck mounted, central office, telephone auto.

**Indicator Type:**

Vibrating reed

**Installation Design:**

Panel

**Register Quantity:**

1

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Dial Scale Marking Color:**

Black single indicator single range

**Resonant Reed Quantity:**

11

**Meter Depth Behind Mounting Flange:**

2.688 inches

**Meter Body Diameter Behind Mounting Flange:**

2.680 inches

**Movement Type:**

Vibrating reed

**Background Color:**

White single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+55.0 to 65.0 hertz single indicator single range

**Criticality Code Justification:**

Feat

**Circuit Attachment Method And Quantity:**

2 solder lug

**Special Features:**

Nuclear hardness critical hardness feature - nonhardened.

**Material:**

Steel

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A310a0