

View Online at <https://aerobasegroup.com/nsn/6625-00-643-3940>

Circuit Current For Which Designed:

Ac

Overall Length:

2.775 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.750 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches

Overall Height:

2.375 inches

Overall Width:

2.375 inches

Mounting Hole Diameter:

0.112 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black and red single indicator single range

Accuracy In Percent:

-1.5 to 1.5 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.625 inches

Meter Body Diameter Behind Mounting Flange:

2.156 inches

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded hole

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

-20.0 to 3.0 decibels above or below one watt single indicator single range

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Circuit Attachment Method And Quantity:

2 threaded stud

Special Markings:

Black from m20 to 0 on div scale; red from @o to p3 on div scale

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0