

View Online at <https://aerobasegroup.com/nsn/6625-00-647-2657>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

1500.0

**Overall Length:**

1.611 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 1.306 inches and 1.318 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.312 inches

**Overall Height:**

1.743 inches

**Overall Width:**

1.747 inches

**Mounting Hole Diameter:**

Between 0.120 inches and 0.130 inches

**Scale Division Quantity:**

2 single indicator single range

**Environmental Protection:**

Shock resistant and vibration resistant

**Furnished Items And Quantity:**

Nut 6; lockwasher 6; seal 1

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

1.0 milliamperes

**Dial Scale Marking Color:**

Black and red single indicator single range

**Accuracy In Percent:**

-3.0 to 3.0 at full scale single indicator single range

**Unable To Decode:**

Unable to decode or unable to decode

**Meter Depth Behind Mounting Flange:**

1.000 inches

**Meter Body Diameter Behind Mounting Flange:**

1.510 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Scale Marking:**

Center scale and end scale marks

**Mounting Facility Type And Quantity:**

4 screw and 4 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Features Provided:**

Magnetic shield and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 solder lug and 2 threaded stud

**Special Features:**

Ruggedized

**Special Markings:**

On back, sealed do not open

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Enamel

**Special Test Features:**

Conforms to mil-m-3823 and mil-m-10304 type mr13w1u1dcmar

**Style Designator:**

Rectangular flush mtg

**Supplementary Features:**

150.0 mv maximum power consumption

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0