

View Online at <https://aerobasegroup.com/nsn/6625-00-648-8361>

Circuit Current For Which Designed:

Dc

Overall Length:

4.062 inches

Overall Height:

5.500 inches

Overall Width:

5.500 inches

Scale Division Quantity:

40 single indicator single range

Mounting Stud Length:

0.500 inches

Distance Between Mounting Facility Centers:

4.750 inches

Furnished Items And Quantity:

External shunt 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

50.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator single range

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

2 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+4000.0 amperes, dc single indicator single range

Mounting Stud Diameter:

0.190 inches

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Plastic window as per specification mil-p-80b

Special Markings:

Red mark at 2800 amp

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular surface mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0