

View Online at <https://aerobasegroup.com/nsn/6625-00-648-8478>

Circuit Current For Which Designed:

Dc

Overall Length:

2.000 inches

Scale Division Quantity:

4 single indicator single range

Mounting Stud Length:

1.0625 inches

Overall Diameter:

2.250 inches

Environmental Protection:

Cold resistant and dustproof and heat resistant and sand proof and shock resistant and vibration resistant and water resistant

Distance Between Mounting Facility Centers:

1.000 inches

Furnished Items And Quantity:

Washer 2; nut 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-10.0/+10.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

0.680 inches

Meter Body Diameter Behind Mounting Flange:

2.030 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

Black single indicator single range

Pointer Color:

White single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 clamp and 2 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

-10.0/+10.0 amperes, dc single indicator single range

Mounting Stud Diameter:

0.190 inches

Scale Selection Method:

Terminal

Features Provided:

Magnetic shield and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Terminal studs used as mounting studs for clamp

Special Markings:

Minus sign; positive sign

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Zinc

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0