

View Online at <https://aerobasegroup.com/nsn/6625-00-648-8729>

Mounting Type:

Portable

Overall Length:

14.000 inches

Overall Height:

10.500 inches

Overall Width:

11.000 inches

Current Type:

Ac

Frequency Rating:

Between 0.05 kilohertz and 1.00 kilohertz

Case Material:

Aluminum

Case Surface Treatment:

Enameled

Frequency Range Rating:

+4.000/+405.000 megahertz

Accessory Component Quantity:

1 and 1 and 1 and 2 and 2 and 1 and 1 and 1 and 1

Accessory Controlling Agency:

Jcens

Accessory Identifying Number:

Cy-1696/urm-26b type no. And cw-365/urm-26b type no. And pp-1215/urm-26b type no. And cg-409a/u /4 ft 1 in./ type no. And cg-409a/u /7 in./ type no. And cu-439/urm-26b type no. And sg-117/urm-26b type no. And cn-315/urm-26b type no. And cn-316/urm-26b type no.

Internal Battery Accommodation:

Not included

Output Impedance Rating:

50.0 ohms

Voltage Rating:

115.0 volts

Frequency Band Quantity:

6

Modulation Type:

Am and am and pulse

Accessory Component Name:

Case; cover; power supply; cord; cord; network, impedance matching; generator, signal; attenuator, fixed; attenuator, fixed

Calibration Accuracy Rating:

Porm 0.5 pct

Calibrated Signal Output Range:

0.1 uv to 100000 uv

Modulator Location:

Any acceptable

Modulated Frequency Rating:

Between 0.4 kilohertz and 1.0 kilohertz and 0.1 kilohertz and 20.0 kilohertz

Pulse Repetition Frequency Rating:

Between 0.05 kilohertz and 5.00 kilohertz

Modulation Degree:

Between 0.0 percent and 50.0 percent and 0.0 percent and 50.0 percent and 1.0 usec pulse and 40.0 usec pulse

Phase:

Single

Reference Number Differentiating Characteristics:

As differentiated by w/repair parts

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T320-j