

View Online at <https://aerobasegroup.com/nsn/6625-00-648-8729>

**Mounting Type:**

Portable

**Overall Length:**

14.000 inches

**Overall Height:**

10.500 inches

**Overall Width:**

11.000 inches

**Current Type:**

Ac

**Frequency Rating:**

Between 0.05 kilohertz and 1.00 kilohertz

**Case Material:**

Aluminum

**Case Surface Treatment:**

Enameled

**Frequency Range Rating:**

+4.000/+405.000 megahertz

**Accessory Component Quantity:**

1 and 1 and 1 and 2 and 2 and 1 and 1 and 1 and 1

**Accessory Controlling Agency:**

Jcens

**Accessory Identifying Number:**

Cy-1696/urm-26b type no. And cw-365/urm-26b type no. And pp-1215/urm-26b type no. And cg-409a/u /4 ft 1 in./ type no. And cg-409a/u /7 in./ type no. And cu-439/urm-26b type no. And sg-117/urm-26b type no. And cn-315/urm-26b type no. And cn-316/urm-26b type no.

**Internal Battery Accommodation:**

Not included

**Output Impedance Rating:**

50.0 ohms

**Voltage Rating:**

115.0 volts

**Frequency Band Quantity:**

6

**Modulation Type:**

Am and am and pulse

**Accessory Component Name:**

Case; cover; power supply; cord; cord; network, impedance matching; generator, signal; attenuator, fixed; attenuator, fixed

**Calibration Accuracy Rating:**

Porm 0.5 pct

**Calibrated Signal Output Range:**

0.1 uv to 100000 uv

**Modulator Location:**

Any acceptable

**Modulated Frequency Rating:**

Between 0.4 kilohertz and 1.0 kilohertz and 0.1 kilohertz and 20.0 kilohertz

**Pulse Repetition Frequency Rating:**

Between 0.05 kilohertz and 5.00 kilohertz

**Modulation Degree:**

Between 0.0 percent and 50.0 percent and 0.0 percent and 50.0 percent and 1.0 usec pulse and 40.0 usec pulse

**Phase:**

Single

**Reference Number Differentiating Characteristics:**

As differentiated by w/repair parts

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T320-j