

View Online at <https://aerobasegroup.com/nsn/6625-00-648-9123>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

3000.0

**Overall Length:**

4.468 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.406 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.406 inches

**Overall Height:**

4.531 inches

**Overall Width:**

4.468 inches

**Frequency Rating:**

60.0 hertz

**Mounting Stud Length:**

0.593 inches

**Environmental Protection:**

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

**Furnished Items And Quantity:**

Nut 4; lockwasher 4; seal 1

**Indicator Type:**

Vibrating reed

**Installation Design:**

Panel

**Register Quantity:**

2

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

150.0 volts

**Dial Scale Marking Color:**

Black single indicator single range

**Resonant Reed Quantity:**

21

**Meter Depth Behind Mounting Flange:**

3.531 inches

**Meter Body Diameter Behind Mounting Flange:**

3.656 inches

**Movement Type:**

Vibrating reed

**Background Color:**

White single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 threaded stud

**Measurement Range:**

+55.0 to 65.0 hertz single indicator single range

**Mounting Stud Diameter:**

0.250 inches

**Scale Selection Method:**

Terminal

**Features Provided:**

Magnetic shield

**Circuit Attachment Method And Quantity:**

2 solder lug

**Operating Voltage Rating In Volts:**

Between 100.0 ac and 150.0 ac

**Special Features:**

Ruggedized; sealed

**Special Markings:**

On back, sealed do not open; calibrated with scale vertical

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Cadmium and chromate

**Special Test Features:**

Complies with mil-m-10304

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A310a0