

View Online at <https://aerobasegroup.com/nsn/6625-00-648-9123>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

4.468 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.406 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.406 inches

Overall Height:

4.531 inches

Overall Width:

4.468 inches

Frequency Rating:

60.0 hertz

Mounting Stud Length:

0.593 inches

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Furnished Items And Quantity:

Nut 4; lockwasher 4; seal 1

Indicator Type:

Vibrating reed

Installation Design:

Panel

Register Quantity:

2

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

150.0 volts

Dial Scale Marking Color:

Black single indicator single range

Resonant Reed Quantity:

21

Meter Depth Behind Mounting Flange:

3.531 inches

Meter Body Diameter Behind Mounting Flange:

3.656 inches

Movement Type:

Vibrating reed

Background Color:

White single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Measurement Range:

+55.0 to 65.0 hertz single indicator single range

Mounting Stud Diameter:

0.250 inches

Scale Selection Method:

Terminal

Features Provided:

Magnetic shield

Circuit Attachment Method And Quantity:

2 solder lug

Operating Voltage Rating In Volts:

Between 100.0 ac and 150.0 ac

Special Features:

Ruggedized; sealed

Special Markings:

On back, sealed do not open; calibrated with scale vertical

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Cadmium and chromate

Special Test Features:

Complies with mil-m-10304

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0