NSN 6625-00-648-9515

Voltmeter - Page 1 of 2

2000.0

Overall Length: 2.170 inches

0.150 inches

Mounting Hole Diameter:

Scale Division Quantity:

Circuit Current For Which Designed:

Dielectric Withstanding Voltage In Volts:



View Online at https://aerobasegroup.com/nsn/6625-00-648-9515

| 30 single indicator all ranges |
|---|
| Overall Diameter: |
| 3.500 inches |
| Mounting Bolt Circle Diameter: |
| 2.440 inches |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Three hole/stud bolt circle |
| Dial Scale Marking Color: |
| Black single indicator all ranges |
| Accuracy In Percent: |
| -2.0 to 2.0 at full scale single indicator all ranges |
| Meter Depth Behind Mounting Flange: |
| 1.790 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.800 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| White single indicator all ranges |
| Pointer Color: |
| Black single indicator all ranges |
| Mounting Facility Type And Quantity: |
| 3 unthreaded hole |
| Scale Graduation Type: |
| Linear single indicator all ranges |
| Measurement Range: |
| +0.0 to 600.0 volts, ac single indicator 2nd range |
| Scale Selection Method: |
| Terminal |

NSN 6625-00-648-9515

Voltmeter - Page 2 of 2



| Movement Suspension Method: |
|---|
| Jewel pivot base |
| Circuit Attachment Method And Quantity: |
| 2 binding post |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Round flush mtg |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No Fiig: A310a0