## NSN 6625-00-648-9784

Voltmeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-648-9784

| Circuit Current For Which Designed:                                       |
|---|
| Ac  |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.375 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 3.375 inches  |
| Overall Height:   |
| 4.421 inches  |
| Overall Width:  |
| 4.421 inches  |
| Mounting Hole Diameter:   |
| 0.250 inches  |
| Installation Design:  |
| Panel   |
| Mounting Arrangement Style:   |
| Four hole/stud rectangular/square   |
| Sensitivity Rating:   |
| 18180.0 ohms per volt   |
| Dial Scale Marking Color:   |
| Black single indicator single range                                       |
| Accuracy In Percent:  |
| -1.0/+1.0 at full scale single indicator all ranges                       |
| Meter Depth Behind Mounting Flange:                                       |
| 2.813 inches  |
| Meter Body Diameter Behind Mounting Flange:                               |
| 3.960 inches  |
| Background Color:   |
| White single indicator single range                                       |
| Mounting Facility Type And Quantity:                                      |
| 1 flange  |
| Measurement Range:  |
| +0.0/+250.0 volts, ac single indicator single range                       |
| Features Provided:  |
| Nonglare glass  |
| Circuit Attachment Method And Quantity:                                   |
| 2 binding post  |
| Style Designator:   |
| Rectangular flush mtg   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |

--

## NSN 6625-00-648-9784

Voltmeter - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A310a0