NSN 6625-00-649-0404

Ammeter - Page 1 of 2

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-649-0404

| AC |
|---|
| Overall Length: |
| 1.943 inches |
| Mounting Hole Diameter: |
| 0.125 inches |
| Scale Division Quantity: |
| 21 single indicator single range |
| Overall Diameter: |
| 2.695 inches |
| Mounting Bolt Circle Diameter: |
| 2.440 inches |
| Furnished Items And Quantity: |
| Mounting hardware 6 |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Three hole/stud bolt circle |
| Frequency Response Range: |
| +1.000/+500.000 hertz |
| Sensitivity Rating: |
| 900.0 millivolts |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -0.05/+0.05 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 1.063 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.150 inches |
| Movement Type: |
| Moving iron vane |
| Background Color: |
| White single indicator single range |
| Pointer Color: |
| Black single indicator single range |
| Power Source: |
| External |
| Mounting Facility Type And Quantity: |
| 3 screw and 3 unthreaded hole |

NSN 6625-00-649-0404

Ammeter - Page 2 of 2



| Scale Graduation Type: |
|---|
| Linear single indicator single range |
| Measurement Range: |
| +0.0/+75.0 milliamperes, ac single indicator single range |
| Features Provided: |
| Zero adjuster |
| Movement Suspension Method: |
| Taut band |
| Circuit Attachment Method And Quantity: |
| 2 solder stud |
| Special Features: |
| Hermetically sealed |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Round flush mtg |
| Fsc Application Data: |
| Test set, elect. Equip. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A310a0 |