

View Online at <https://aerobasegroup.com/nsn/6625-00-649-1903>

Circuit Current For Which Designed:

Dc

Overall Length:

2.030 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.856 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.856 inches

Overall Height:

2.380 inches

Overall Width:

2.380 inches

Scale Division Quantity:

20 single indicator single range

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

50.0 millivolts

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

0.830 inches

Meter Body Diameter Behind Mounting Flange:

2.250 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

Black single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

1 flange

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+20.0 amperes, dc single indicator single range

Scale Selection Method:

Switch

Features Provided:

Magnetic shield and self-illumination facility

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 binding post

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set electronic

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0