## NSN 6625-00-649-2036

Signal Generator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-649-2036

Mounting Type:
Portable
Overall Length:
17.000 inches
Overall Height:
17.625 inches
Overall Width:
14.000 inches
Current Type:
Ac
Frequency Rating:
50.0 hertz
Case Material:
Metal
Case Surface Treatment:
Lacquer baked-on over zinc coated
Frequency Range Rating:
+3800.000/+7500.000 megahertz
Accessory Component Quantity:
1 and 1 and 1
Accessory Controlling Agency:
Jcens; jcens; jcens
Accessory Identifying Number:
Cy-1294/u type no. And cx-337/u type no. And cg-409/u type no. And cg-92d/u type no.
Internal Battery Accommodation:
Not included
Output Impedance Rating:
52.0 ohms
Voltage Rating:
115.0 volts
Frequency Band Quantity:
1
Modulation Type:
Fm and pulse
Accessory Component Name:
Transit case 1; power cord 1; videocable 1; rf cable
Calibration Accuracy Rating:
Porm 1 percent accuracy of calibration
Crystal Controlled Feature:
Not provided

riot providod

**Calibrated Signal Output Range:** 

0.1 to 72.000 uv calibrated output

## NSN 6625-00-649-2036

Signal Generator - Page 2 of 2



Signal Output Constancy:
Porm 2 db maximum variation through frequency range
Modulator Location:
Internal
Modulated Frequency Rating:
40.0 hertz and 400.0 hertz
Pulse Repetition Frequency Rating:
4.0 hertz
Modulation Degree:
3.0 percent
Phase:
Single
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: T320-j