NSN 6625-00-649-2864

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-649-2864

Circuit Current For Which Designed:
Ac
Overall Length:
2.625 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.856 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.856 inches
Overall Height:
2.375 inches
Overall Width:
2.375 inches
Mounting Hole Diameter:
0.112 inches
Scale Division Quantity:
50 single indicator single range
Environmental Protection:
Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and
water resistant
End Application:
Aircraft hercules c-130, starlifter c-141, support equipment aircraft f-16, f-106, so (ac-130h, mc-130h, ec-130e, hc-130)
Furnished Items And Quantity:
Nut 8; lockwasher 6; seal 1
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Dial Scale Marking Color:
Yellow single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
1.375 inches
Meter Body Diameter Behind Mounting Flange:
2.060 inches
Movement Type:
Moving iron vane
Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

NSN 6625-00-649-2864 Ammeter - Page 2 of 2



Power Source:
External
Mounting Facility Type And Quantity:
4 unthreaded hole
Scale Graduation Type:
Linear single indicator single range
Measurement Range:
+0.0/+100.0 amperes, ac single indicator single range
Features Provided:
Zero adjuster
Criticality Code Justification:
Feat
Movement Suspension Method:
Taut band
Circuit Attachment Method And Quantity:
2 solder lug and 2 threaded stud
Special Features:
Weapon system essential
Material:
Plastic
Surface Treatment:
Paint
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A310a0