

View Online at <https://aerobasegroup.com/nsn/6625-00-649-3918>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

2.400 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.874 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.874 inches

**Overall Height:**

2.370 inches

**Overall Width:**

2.370 inches

**Scale Division Quantity:**

50 single indicator single range

**Mounting Stud Length:**

0.530 inches

**Furnished Items And Quantity:**

Nut 2

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator single range

**Unable To Decode:**

Unable to decode or unable to decode

**Meter Depth Behind Mounting Flange:**

1.450 inches

**Meter Body Diameter Behind Mounting Flange:**

2.180 inches

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 threaded stud

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+0.0 to 50.0 volts, dc single indicator single range

**Mounting Stud Diameter:**

0.112 inches

**Features Provided:**

Zero adjuster

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

1000 ohm per v meter resistance

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Supplementary Features:**

Self-shielding movement

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0