

View Online at <https://aerobasegroup.com/nsn/6625-00-649-3985>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

1.187 inches

Scale Division Quantity:

20 single indicator single range

Overall Diameter:

1.250 inches

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Furnished Items And Quantity:

Seal 1; ring 1; wire shunt 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

20000.0 volts

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

0.687 inches

Meter Body Diameter Behind Mounting Flange:

1.000 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

Black single indicator single range

Pointer Color:

White single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 threaded body

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 20.0 kilovolts single indicator single range

Scale Selection Method:

Terminal

Features Provided:

External shunting

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 screw and 2 solder lug

Special Features:

Ruggedized

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Special Test Features:

Complies with mil-m-10304

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0