

View Online at <https://aerobasegroup.com/nsn/6625-00-649-4001>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

1500.0

**Overall Length:**

2.265 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.875 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.875 inches

**Overall Height:**

2.375 inches

**Overall Width:**

2.375 inches

**Mounting Hole Diameter:**

0.140 inches

**Environmental Protection:**

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

**Furnished Items And Quantity:**

Nut 8; lockwasher 6; seal 1

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Frequency Response Range:**

+0.000 to 400.000 hertz

**Sensitivity Rating:**

250.0 volts

**Dial Scale Marking Color:**

Yellow single indicator single range

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

1.031 inches

**Meter Body Diameter Behind Mounting Flange:**

2.234 inches

**Movement Type:**

Moving iron vane

**Background Color:**

Black single indicator single range

**Pointer Color:**

Yellow single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 screw and 4 unthreaded hole

**Scale Graduation Type:**

Nonlinear single indicator single range

**Measurement Range:**

+0.0 to 250.0 volts, ac single indicator single range

**Scale Selection Method:**

Terminal

**Features Provided:**

Magnetic shield and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Operating Voltage Rating In Volts:**

250.0 ac

**Special Features:**

Ruggedized

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Paint

**Special Test Features:**

Complies with mil-m-10304

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0