NSN 6625-00-649-4078

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-649-4078

Circuit Current For Which Designed: Dc **Dielectric Withstanding Voltage In Volts:** 3000.0 **Overall Length:** 2.850 inches **Scale Division Quantity:** 20 single indicator single range Mounting Stud Length: 0.500 inches **Overall Diameter:** 3.510 inches **Environmental Protection:** Cold resistant and heat resistant and shock resistant and submersible and vibration resistant and watertight Mounting Bolt Circle Diameter: 3.160 inches

Furnished Items And Quantity:

Mtg hdw 3

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

150.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

2.450 inches

Meter Body Diameter Behind Mounting Flange:

2.800 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

NSN 6625-00-649-4078

Ammeter - Page 2 of 2



Power Source: External Mounting Facility Type And Quantity: 3 threaded stud Scale Graduation Type: Linear single indicator single range **Measurement Range:** +0.0/+2.0 milliamperes, dc single indicator single range **Mounting Stud Diameter:** 0.138 inches **Scale Selection Method:** Terminal **Features Provided:** Luminous scale marking and magnetic shield and zero adjuster **Movement Suspension Method:** Jewel pivot base **Circuit Attachment Method And Quantity:** 2 solder stud and 2 threaded stud **Special Features:** Ruggedized Material: Steel **Nuclear Hardness Critical Feature:** Nonhardened Style Designator: Round flush mtg **Test Data Document:** 81349-mil-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 81349-mil-m-10304/12 government specification **Fsc Application Data:** Test set, elect. Equip. Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0