NSN 6625-00-649-4189

Voltmeter - Page 1 of 2

1.968 inches

1.968 inchesOverall Height:2.375 inchesOverall Width:2.375 inches

0.125 inches

Panel

Mounting Hole Diameter:

Mounting Arrangement Style: Four hole/stud rectangular/square Frequency Response Range:

Installation Design:

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-649-4189

Center To Center Distance Between Mounting Facilities Parallel To Length:

Center To Center Distance Between Mounting Facilities Parallel To Width:

| +330.000/+440.000 hertz | | | | | | | |
|---|--|--|--|--|--|--|--|
| Dial Scale Marking Color: | | | | | | | |
| White single indicator single range | | | | | | | |
| Accuracy In Percent: | | | | | | | |
| -2.0/+2.0 at full scale single indicator all ranges | | | | | | | |
| Meter Depth Behind Mounting Flange: | | | | | | | |
| 1.812 inches | | | | | | | |
| Meter Body Diameter Behind Mounting Flange: | | | | | | | |
| 2.187 inches | | | | | | | |
| Background Color: | | | | | | | |
| Black single indicator single range | | | | | | | |
| Mounting Facility Type And Quantity: | | | | | | | |
| 4 unthreaded hole | | | | | | | |
| Measurement Range: | | | | | | | |
| +0.0/+150.0 volts, ac single indicator single range | | | | | | | |
| Features Provided: | | | | | | | |
| Magnetic shield | | | | | | | |
| Circuit Attachment Method And Quantity: | | | | | | | |
| 1 threaded stud | | | | | | | |
| Material: | | | | | | | |
| Plastic | | | | | | | |
| Radioactive Content: | | | | | | | |
| Contains radioactive material | | | | | | | |
| Style Designator: | | | | | | | |
| Round flush mtg w/4 tabs | | | | | | | |

NSN 6625-00-649-4189

Voltmeter - Page 2 of 2



| _ | | | | | |
|----|---|---|----|----|----|
| ٠. | n | _ | I+ | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0