

View Online at <https://aerobasegroup.com/nsn/6625-00-649-4287>

Circuit Current For Which Designed:

Ac

Overall Length:

3.406 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.200 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.200 inches

Overall Height:

3.250 inches

Overall Width:

3.250 inches

Mounting Hole Diameter:

0.138 inches

Scale Division Quantity:

50 single indicator single range

Frequency Rating:

60.000 hertz

Environmental Protection:

Dustproof and shock proof and waterproof

Furnished Items And Quantity:

Locking mtg insert 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Frequency Response Range:

+375.0 to 425.0 hertz

Sensitivity Rating:

0.8 volt-amperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-0.33 to 0.33 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

3.28125 inches

Meter Body Diameter Behind Mounting Flange:

3.125 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+375.0 to 425.0 hertz single indicator single range

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Metal pivot base

Circuit Attachment Method And Quantity:

1 connector, receptacle

Operating Voltage Rating In Volts:

Between 100.0 ac and 125.0 ac

Phase:

Single

Special Features:

Ruggedized

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiiig:

A310a0