

View Online at <https://aerobasegroup.com/nsn/6625-00-649-4560>

Circuit Current For Which Designed:

Ac

Overall Length:

1.983 inches

Mounting Hole Diameter:

0.150 inches

Scale Division Quantity:

15 single indicator single range

Overall Diameter:

3.510 inches

Environmental Protection:

Airtight and cold resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant

Mounting Bolt Circle Diameter:

3.160 inches

Furnished Items And Quantity:

Nut 3; washer 3

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Frequency Response Range:

+0.050 to 1.600 kilohertz

Sensitivity Rating:

64000.0 ohms per volt

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.063 inches

Meter Body Diameter Behind Mounting Flange:

2.680 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+75.0 to 150.0 volts, ac single indicator single range

Features Provided:

Zero adjuster

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Special Markings:

Green band from 103v to 127v; above band mark normal

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiiig:

A310a0