

View Online at <https://aerobasegroup.com/nsn/6625-00-649-4658>

**Width:**

20.625 inches

**Length:**

21.375 inches

**Ac Voltage Rating:**

115.0 volts

**Frequency Rating:**

Between 50.0 hertz and 1000.0 hertz

**Major Components:**

Cabinet; cable; cable; case; delay line; delay line; delay line; delay line; delay line; indicator; power supply

**Accessory Component Quantity:**

1 and 1

**Accessory Controlling Agency:**

Jcens

**Accessory Identifying Number:**

Cy-1319/upm type no. And cg-546/u type no. And cg-579/u type no. And cy-1318/upm type no. And mx-1448/up type no. And mx-1449/up type no. And mx-1450/up type no. And mx-1451/up type no. And mx-1452/up type no. And ts-577/up type no. And pp-910/upm type no.

**Internal Battery Accommodation:**

Not included

**Material And Location:**

Aluminum carrying case

**Inclosure Feature:**

Multiple item w/carrying case

**Test Type For Which Designed:**

Measure subclutter visibility at if; phase detector characteristics; if, video pulse jitter; continuous wave, pulsed if of signal generator

**Operating Test Capability:**

Signal generator; range 27 to 33 megacycles, output 22.4 microvolts to 224 millivolts, pulse repetition frequency 50 to 6000 cycles, pulse jitter tester, sine wave sweep frequency 258 kc, range 27 to 33 megacycles, form 10 per cent accuracy

**Phase:**

Single

**Height:**

33.437 inches

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T228-a