Electrical Frequency Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-649-4724

View Online at https://aerobasegroup.com/nsn/6625-00-649-4724
Circuit Current For Which Designed:
Ac
Dielectric Withstanding Voltage In Volts:
1500.0
Overall Length:
3.345 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.250 inches
Overall Height:
3.125 inches
Overall Width:
3.000 inches
Frequency Rating:
Between 380.0 hertz and 420.0 hertz
Mounting Stud Length:
0.500 inches
Environmental Protection:
Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and
water resistant
Furnished Items And Quantity:
Nut 10; lockwasher 4; flat washer 4; seal 1
Indicator Type:
Vibrating reed
Installation Design:
Panel
Register Quantity:
1
Mounting Arrangement Style:
Four hole/stud rectangular/square
Frequency Response Range:
+380.000 to 420.000 hertz
Dial Scale Marking Color:
Black single indicator single range
Resonant Reed Quantity:
11
Meter Depth Behind Mounting Flange:
2.312 inches
Meter Body Diameter Behind Mounting Flange:
2.800 inches
Movement Type:
Vibrating read

Vibrating reed



Background Color:
White single indicator single range
Power Source:
External
Mounting Facility Type And Quantity:
4 threaded stud
Measurement Range:
+380.0 to 420.0 hertz single indicator single range
Mounting Stud Diameter:
0.112 inches
Scale Selection Method:
Terminal
Features Provided:
Magnetic shield
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Operating Voltage Rating In Volts:
150.0 ac
Special Features:
Ruggedized
Material:
Plastic
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Paint
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0