NSN 6625-00-649-4741

Modulation Meter - Page 1 of 2

Circuit Current For Which Designed:

Dc

Overall Length: 1.875 inches

0.140 inches

Mounting Hole Diameter:

Scale Division Quantity:
15 single indicator 1st range

Overall Diameter:



View Online at https://aerobasegroup.com/nsn/6625-00-649-4741

| 3.500 inches | |
|--|--|
| Mounting Bolt Circle Diameter: | |
| 3.160 inches | |
| Indicator Type: | |
| Dial w/pointer | |
| Installation Design: | |
| Panel | |
| Mounting Arrangement Style: | |
| Three hole/stud bolt circle | |
| Sensitivity Rating: | |
| 100.0 microamperes | |
| Dial Scale Marking Color: | |
| Black single indicator all ranges | |
| Accuracy In Percent: | |
| -2.0 to 2.0 at full scale single indicator all ranges | |
| Meter Depth Behind Mounting Flange: | |
| 1.063 inches | |
| Meter Body Diameter Behind Mounting Flange: | |
| 2.675 inches | |
| Movement Type: | |
| Moving coil, permanent magnet | |
| Background Color: | |
| White single indicator all ranges | |
| Pointer Color: | |
| Black single indicator all ranges | |
| Power Source: | |
| External | |
| Mounting Facility Type And Quantity: | |
| 3 unthreaded hole | |
| Scale Graduation Type: | |
| Nonlinear single indicator 2nd range | |
| Measurement Range: | |
| +0.0 to 30.0 percent modulation single indicator 1st range | |

NSN 6625-00-649-4741Modulation Meter - Page 2 of 2



| Scale Selection Method: |
|--|
| Terminal |
| Features Provided: |
| Zero adjuster |
| Movement Suspension Method: |
| Jewel pivot base |
| Circuit Attachment Method And Quantity: |
| 2 solder lug |
| Special Features: |
| Ruggedized.Panel for which designed is magnetic.Circuit construction type is non-electronic. |
| Material: |
| Steel |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Surface Treatment: |
| Enamel |
| Style Designator: |
| Round flush mtg |
| Fsc Application Data: |
| Test set, elect. Equip. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A310a0 |
| |
| |