

View Online at <https://aerobasegroup.com/nsn/6625-00-649-4768>

Circuit Current For Which Designed:

Ac

Overall Length:

3.060 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.470 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.470 inches

Overall Height:

3.250 inches

Overall Width:

3.250 inches

Mounting Hole Diameter:

0.170 inches

Scale Division Quantity:

50 single indicator single range

Furnished Items And Quantity:

Nut 6; washer 6

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.310 inches

Meter Body Diameter Behind Mounting Flange:

3.130 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 screw and 4 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+350.0 to 450.0 hertz single indicator single range

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg w/4 tabs

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

FiiG:

A310a0