

View Online at <https://aerobasegroup.com/nsn/6625-00-649-4860>

Circuit Current For Which Designed:

Ac

Overall Length:

3.343 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.250 inches

Overall Height:

3.125 inches

Overall Width:

3.000 inches

Frequency Rating:

400.0 hertz

Mounting Stud Length:

0.500 inches

Furnished Items And Quantity:

Mtg hdw 4; term. Hdw 2

Indicator Type:

Vibrating reed

Installation Design:

Panel

Register Quantity:

1

Mounting Arrangement Style:

Four hole/stud rectangular/square

Frequency Response Range:

+10.000 to 600.000 hertz

Sensitivity Rating:

100.0 ohms per volt

Resonant Reed Quantity:

11

Meter Depth Behind Mounting Flange:

3.060 inches

Meter Body Diameter Behind Mounting Flange:

2.790 inches

Movement Type:

Vibrating reed

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Measurement Range:

+380.0 to 420.0 hertz single indicator single range

Mounting Stud Diameter:

0.112 inches

Scale Selection Method:

Terminal

Circuit Attachment Method And Quantity:

2 threaded stud

Operating Voltage Rating In Volts:

Between 100.0 ac and 150.0 ac

Phase:

Single

Special Features:

Ruggedized

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0