

View Online at <https://aerobasegroup.com/nsn/6625-00-649-4860>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

3.343 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.250 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.250 inches

**Overall Height:**

3.125 inches

**Overall Width:**

3.000 inches

**Frequency Rating:**

400.0 hertz

**Mounting Stud Length:**

0.500 inches

**Furnished Items And Quantity:**

Mtg hdw 4; term. Hdw 2

**Indicator Type:**

Vibrating reed

**Installation Design:**

Panel

**Register Quantity:**

1

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Frequency Response Range:**

+10.000 to 600.000 hertz

**Sensitivity Rating:**

100.0 ohms per volt

**Resonant Reed Quantity:**

11

**Meter Depth Behind Mounting Flange:**

3.060 inches

**Meter Body Diameter Behind Mounting Flange:**

2.790 inches

**Movement Type:**

Vibrating reed

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 threaded stud

**Measurement Range:**

+380.0 to 420.0 hertz single indicator single range

**Mounting Stud Diameter:**

0.112 inches

**Scale Selection Method:**

Terminal

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Operating Voltage Rating In Volts:**

Between 100.0 ac and 150.0 ac

**Phase:**

Single

**Special Features:**

Ruggedized

**Material:**

Plastic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0