

View Online at <https://aerobasegroup.com/nsn/6625-00-649-4886>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

30000.0

Overall Length:

1.875 inches

Mounting Hole Diameter:

0.100 inches

Frequency Rating:

400.0 hertz

Overall Diameter:

2.100 inches

Mounting Bolt Circle Diameter:

1.740 inches

Indicator Type:

Vibrating reed

Installation Design:

Panel

Register Quantity:

1

Mounting Arrangement Style:

Three hole/stud bolt circle

Frequency Response Range:

+380.000 to 420.000 hertz

Resonant Reed Quantity:

5

Meter Depth Behind Mounting Flange:

1.560 inches

Meter Body Diameter Behind Mounting Flange:

1.510 inches

Movement Type:

Vibrating reed

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Measurement Range:

+380.0 to 420.0 hertz single indicator single range

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Circuit Attachment Method And Quantity:

2 solder stud

Operating Voltage Rating In Volts:

125.0 ac

Phase:

Single

Special Features:

Ruggedized

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0