

View Online at <https://aerobasegroup.com/nsn/6625-00-649-4938>

Circuit Current For Which Designed:

Ac

Overall Length:

2.130 inches

Mounting Hole Diameter:

0.204 inches

Scale Division Quantity:

50 single indicator 7th range

Overall Diameter:

4.570 inches

Mounting Bolt Circle Diameter:

4.120 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

50.0 microamperes

Dial Scale Marking Color:

Green single indicator 1st range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.375 inches

Meter Body Diameter Behind Mounting Flange:

3.620 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator 4th range

Measurement Range:

+0.0 to 5000.0 ohms single indicator 1st range

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 solder stud

Special Features:

Ruggedized

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Supplementary Features:

Internal resistance shall be 1700 ohms plus or minus 2 percent

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0