

View Online at <https://aerobasegroup.com/nsn/6625-00-649-4989>

Overall Length:

29.000 inches

Overall Height:

9.750 inches

Overall Width:

12.750 inches

Current Type:

Ac

Frequency Rating:

50.0 hertz

End Application:

Type no. Scr-682

Accessory Components And Quantity:

Cords 5; probes 2

Voltage Rating:

115.0 volts

Beam Quantity:

1

Mounting Method:

Table

Screen Size:

2.000 inches

Sweep Circuits:

Included

Generator Driven Feature:

Not included

Sweep Circuit Type:

Horizontal and vertical

Sweep Frequency Range:

+30.000/+1000000.000 hertz

Single Trigger Sweep Duration:

Between 0.1 microseconds and 1.0 microseconds

Trigger Sweep Voltage Amplitude Rating:

13.0 volts

Trigger Sweep Polarity Switch:

Not included

Trigger Sweep Marker Intervals:

0.2 usec

Expanded Sweep:

Not provided

Amplifier Deflection Sensitivity Provision:

Provided

Vertical Deflection Sensitivity Voltage Rating:

196.0 volts rms per inch

Horizontal Deflection Sensitivity Voltage Rating:

230.0 volts any acceptable outside diameter

Input Intensity Modulation Feature:

Not provided

Plate Direct Connection Deflection Sensitivity Provision:

Provided

Direct Connection Vertical Deflection Sensitivity Voltage Rating:

196.0 volts any acceptable outside diameter

Direct Connection Horizontal Deflection Sensitivity Voltage Rating:

230.0 volts rms per inch

Frequency Response Rating:

Provided

X-axis Frequency Response Rating:

Between 4.5 hertz and 8.0 hertz

Y-axis Frequency Response Rating:

Between 20.0 hertz and 50.0 hertz

Z-axis Frequency Response Rating:

Between 120.0 hertz and 280.0 hertz

Amplifier Input Impedance Rating Provision:

Provided

X-axis Input Impedance Rating:

62.0 ohms

Y-axis Input Impedance Rating:

62.0 ohms

Z-axis Input Impedance Rating:

62.0 ohms

Calibrated Screen Scale:

Not included

Trace Storage Tube:

Not included

Camera Recording Device Accommodation:

Not provided

Phase:

Single

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T320-g