

View Online at <https://aerobasegroup.com/nsn/6625-00-649-5193>

**Mounting Type:**

Portable case

**Overall Length:**

14.000 inches

**Overall Height:**

10.500 inches

**Overall Width:**

11.000 inches

**Current Type:**

Ac

**Frequency Rating:**

Between 50.0 hertz and 1600.0 hertz

**Case Material:**

Aluminum

**Case Surface Treatment:**

Enamel

**Frequency Range Rating:**

+0.010/+50.000 megahertz

**Accessory Component Quantity:**

8

**Accessory Controlling Agency:**

Trad television cory

**Accessory Identifying Number:**

Su-85/urm-25d type no. And cn-224/urm-25d type no. And cn-223/urm-25d type no. And mx-1487/urm-25d type no. And cx-1383/u type no. And pp-977/urm-25d type no. And sm-35/urm-25 type no. And cg-409/u type no.

**Joint Electronics Type Designation System Item Name:**

Rf signal generato r set

**Joint Electronics Type Designation System Item Type Number:**

An/urm-25d

**Output Impedance Rating:**

Between 53.5 ohms and 500.0 ohms

**Voltage Rating:**

115.0 volts

**Frequency Band Quantity:**

8

**Modulation Type:**

Pulse

**Accessory Component Name:**

Navy gen erator signal, attenuator fixed, attenuator fixed, adpter test, test lead power supply, antenna simulator, cord,

**Calibration Accuracy Rating:**

Porm 0.5 percent accuracy of calibration

**Crystal Controlled Feature:**

Provided

**Maximum Signal Output:**

0.1 uv to 100000.0 uv

**Modulator Location:**

External

**Modulated Frequency Rating:**

400.000 hertz and 1000.0 kilohertz

**Modulation Degree:**

Between 0.0 percent and 80.0 percent

**Phase:**

Single

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

T320-j