

View Online at <https://aerobasegroup.com/nsn/6625-00-649-5224>

Circuit Current For Which Designed:

Ac and dc

Overall Length:

2.0625 inches

Mounting Hole Diameter:

0.150 inches

Scale Division Quantity:

30 single indicator 1st range

Overall Diameter:

3.488 inches

Mounting Bolt Circle Diameter:

3.160 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

50.0 microamperes

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.90625 inches

Meter Body Diameter Behind Mounting Flange:

2.710 inches

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator 2nd range

Measurement Range:

+0.0 to 3.0 milliwatts single indicator 1st range

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Circuit Attachment Method And Quantity:

2 threaded stud and 2 wire lead

Special Markings:

Vac marked on both sides of scale

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0