

View Online at <https://aerobasegroup.com/nsn/6625-00-649-5346>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

2.850 inches

Mounting Hole Diameter:

Between 0.143 inches and 0.157 inches

Overall Diameter:

3.510 inches

Environmental Protection:

Cold resistant and heat resistant and shock resistant and submersible and vibration resistant and watertight

Mounting Bolt Circle Diameter:

3.160 inches

Furnished Items And Quantity:

Nut 7; lockwasher 5; seal 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Frequency Response Range:

+25.000/+125.000 hertz

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.660 inches

Meter Body Diameter Behind Mounting Flange:

2.800 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+0.0/+3.0 amperes, ac single indicator single range

Scale Selection Method:

Terminal

Features Provided:

Luminous scale marking and magnetic shield and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug and 2 threaded stud

Special Features:

Ruggedized

Special Markings:

On back, sealed do not open

Material:

Stainless steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel semigloss

Special Test Features:

Environmentals per mil-std-202

Surface Treatment Specification:

Mil-f-14072 military specification single treatment response

Style Designator:

Round flush mtg

Test Data Document:

81349-mil-m-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-m-10304/14 government specification

Fsc Application Data:

Electrical, electronic properties measuring and test instruments

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

4612-6

Mil-std (military Standard):

Mil-f-14072 spec.