

View Online at <https://aerobasegroup.com/nsn/6625-00-649-9279>

Circuit Current For Which Designed:

Dc

Overall Length:

2.063 inches

Mounting Hole Diameter:

0.150 inches

Scale Division Quantity:

50 single indicator 2nd range

Overall Diameter:

3.500 inches

Mounting Bolt Circle Diameter:

3.160 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

200.0 microamperes

Dial Scale Marking Color:

Red single indicator 1st range

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.375 inches

Meter Body Diameter Behind Mounting Flange:

2.750 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Scale Marking:

Calibration level; 0; .2; .4; .6; .8; 1; rf power mw; 0; .2; .4; .6; .8; 1; 0; 10; 20; 30; 40; 50

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator 1st range

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

68 ohms resistance

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0