

View Online at <https://aerobasegroup.com/nsn/6625-00-649-9284>

Overall Length:

13.500 inches

Overall Height:

9.000 inches

Overall Width:

6.000 inches

Current Type:

Ac

Frequency Rating:

Between 50.0 hertz and 1.0 kilohertz

Accessory Components And Quantity:

1 test lead (3 ft), 1 test lead (6 in.), 1 ground lead (3 ft), 1 oscilloscope case, 1 cathode ray tube scale, 1 instruction book

Voltage Rating:

115.0 volts

Beam Quantity:

1

Screen Size:

3 in.

Sweep Circuits:

Included

Generator Driven Feature:

Not included

Sweep Frequency Range:

+3.000/+50000.000 hertz

Amplifier Deflection Sensitivity Provision:

Provided

Vertical Deflection Sensitivity Voltage Rating:

75.0 millivolts rms per inch

Horizontal Deflection Sensitivity Voltage Rating:

75.0 millivolts any acceptable outside diameter

Input Intensity Modulation Feature:

Not provided

Plate Direct Connection Deflection Sensitivity Provision:

Provided

Direct Connection Vertical Deflection Sensitivity Voltage Rating:

17.0 volts any acceptable outside diameter

Direct Connection Horizontal Deflection Sensitivity Voltage Rating:

25.0 volts rms per inch

Frequency Response Rating:

Provided

X-axis Frequency Response Rating:

Between 0.0 hertz and 2000000.0 hertz

Y-axis Frequency Response Rating:

Between 5.0 hertz and 2000000.0 hertz

Amplifier Input Impedance Rating Provision:

Provided

X-axis Input Impedance Rating:

1.5 megohms

Y-axis Input Impedance Rating:

1.5 megohms

Calibrated Screen Scale:

Not included

Trace Storage Tube:

Not included

Camera Recording Device Accommodation:

Not provided

Phase:

Single

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T320-g