

View Online at <https://aerobasegroup.com/nsn/6625-00-649-9284>

**Overall Length:**

13.500 inches

**Overall Height:**

9.000 inches

**Overall Width:**

6.000 inches

**Current Type:**

Ac

**Frequency Rating:**

Between 50.0 hertz and 1.0 kilohertz

**Accessory Components And Quantity:**

1 test lead (3 ft), 1 test lead (6 in.), 1 ground lead (3 ft), 1 oscilloscope case, 1 cathode ray tube scale, 1 instruction book

**Voltage Rating:**

115.0 volts

**Beam Quantity:**

1

**Screen Size:**

3 in.

**Sweep Circuits:**

Included

**Generator Driven Feature:**

Not included

**Sweep Frequency Range:**

+3.000/+50000.000 hertz

**Amplifier Deflection Sensitivity Provision:**

Provided

**Vertical Deflection Sensitivity Voltage Rating:**

75.0 millivolts rms per inch

**Horizontal Deflection Sensitivity Voltage Rating:**

75.0 millivolts any acceptable outside diameter

**Input Intensity Modulation Feature:**

Not provided

**Plate Direct Connection Deflection Sensitivity Provision:**

Provided

**Direct Connection Vertical Deflection Sensitivity Voltage Rating:**

17.0 volts any acceptable outside diameter

**Direct Connection Horizontal Deflection Sensitivity Voltage Rating:**

25.0 volts rms per inch

**Frequency Response Rating:**

Provided

**X-axis Frequency Response Rating:**

Between 0.0 hertz and 2000000.0 hertz

**Y-axis Frequency Response Rating:**

Between 5.0 hertz and 2000000.0 hertz

**Amplifier Input Impedance Rating Provision:**

Provided

**X-axis Input Impedance Rating:**

1.5 megohms

**Y-axis Input Impedance Rating:**

1.5 megohms

**Calibrated Screen Scale:**

Not included

**Trace Storage Tube:**

Not included

**Camera Recording Device Accommodation:**

Not provided

**Phase:**

Single

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

T320-g