NSN 6625-00-651-5332

Ammeter - Page 1 of 2

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-651-5332

| Dc |
|---|
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.312 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.312 inches |
| Overall Height: |
| 1.750 inches |
| Overall Width: |
| 1.750 inches |
| Mounting Hole Diameter: |
| 0.125 inches |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Four hole/stud rectangular/square |
| Dial Scale Marking Color: |
| White single indicator single range |
| Accuracy In Percent: |
| -10.0/+10.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 0.812 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 1.312 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| Black single indicator single range |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole |
| Measurement Range: |
| -30.0/+30.0 amperes, dc single indicator single range |
| Movement Suspension Method: |
| Jewel pivot base |
| Circuit Attachment Method And Quantity: |
| 2 solder lug |
| Style Designator: |
| Rectangular flush mtg |
| Shelf Life: |
| N/a |

--

Unit Of Measure:

NSN 6625-00-651-5332

Ammeter - Page 2 of 2



| _ | | •• | • • | | | | |
|----|----|----|-----|-----|-----|---|----|
| וו | em | ш | 112 | rız | 211 | n | ٠. |
| | | | | | | | |

No

Fiig:

A310a0