

View Online at <https://aerobasegroup.com/nsn/6625-00-654-9772>

Circuit Current For Which Designed:

Ac

Overall Length:

2.340 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.53125 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.53125 inches

Overall Height:

3.265 inches

Overall Width:

3.265 inches

Mounting Hole Diameter:

0.125 inches

Scale Division Quantity:

60 single indicator single range

Frequency Rating:

400.0 hertz

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Frequency Response Range:

+350.000 to 450.000 hertz

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.980 inches

Meter Body Diameter Behind Mounting Flange:

3.130 inches

Background Color:

Black single indicator single range

Pointer Color:

White single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+350.0 to 450.0 hertz single indicator single range

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Circuit Attachment Method And Quantity:

1 connector, receptacle

Operating Voltage Rating In Volts:

Between 100.0 ac and 125.0 ac

Phase:

Single

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Anodize

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0