

View Online at <https://aerobasegroup.com/nsn/6625-00-658-3402>

Circuit Current For Which Designed:

Ac

Overall Length:

2.6615 inches

Mounting Hole Diameter:

0.125 inches

Frequency Rating:

400.0 hertz

Overall Diameter:

3.500 inches

Mounting Bolt Circle Diameter:

3.160 inches

Indicator Type:

Vibrating reed

Installation Design:

Panel

Register Quantity:

5

Mounting Arrangement Style:

Three hole/stud bolt circle

Frequency Response Range:

+380.000 to 420.000 hertz

Resonant Reed Quantity:

9

Meter Depth Behind Mounting Flange:

2.500 inches

Meter Body Diameter Behind Mounting Flange:

2.780 inches

Movement Type:

Vibrating reed

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Measurement Range:

+380.0 to 420.0 hertz single indicator single range

Scale Selection Method:

Terminal

Circuit Attachment Method And Quantity:

2 solder lug and 2 threaded stud

Operating Voltage Rating In Volts:

Between 100.0 ac and 130.0 ac

Phase:

Single

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0