

View Online at <https://aerobasegroup.com/nsn/6625-00-668-6197>

Overall Length:

21.500 inches

Overall Height:

16.500 inches

Overall Width:

13.500 inches

Current Type:

Ac

Frequency Rating:

Between 50.0 hertz and 1.6 kilohertz

Voltage Rating:

115.0 volts

Beam Quantity:

1

Mounting Method:

Table

Screen Size:

3 in.

Sweep Circuits:

Included

Generator Driven Feature:

Not included

Single Trigger Sweep Duration:

Between 0.5 microseconds and 50.0 milliseconds

Trigger Sweep Voltage Amplitude Rating:

25.0 volts

Trigger Sweep Polarity Switch:

Included

Trigger Sweep Marker Intervals:

0.2, 1, 10, 100, and 500 usec

Expanded Sweep:

Not provided

Amplifier Deflection Sensitivity Provision:

Provided

Input Intensity Modulation Feature:

Not provided

Plate Direct Connection Deflection Sensitivity Provision:

Provided

Direct Connection Vertical Deflection Sensitivity Voltage Rating:

110.0 volts any acceptable outside diameter

Frequency Response Rating:

Provided

X-axis Frequency Response Rating:

Between 10.0 hertz and 5000000.0 hertz

Y-axis Frequency Response Rating:

Between 10.0 hertz and 10000.0 hertz

Amplifier Input Impedance Rating Provision:

Provided

X-axis Input Impedance Rating:

300.0 kilohms

Y-axis Input Impedance Rating:

1.0 megohms

Calibrated Screen Scale:

Not included

Trace Storage Tube:

Not included

Camera Recording Device Accommodation:

Not provided

Phase:

Single

Special Features:

0.01 to 100 v rms per 0.6 in. Vertical deflection sensitivity voltage; 0.01 to 100 v rms per 0.6 in. Horizontal deflection sensitivity voltage

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T320-g