# NSN 6625-00-668-7400

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-668-7400

## Circuit Current For Which Designed:

Dc

## Dielectric Withstanding Voltage In Volts:

3000.0

## **Overall Length:**

2.850 inches

## Scale Division Quantity:

15 single indicator single range

## Mounting Stud Length:

0.500 inches

## **Overall Diameter:**

3.510 inches

## **Environmental Protection:**

Cold resistant and heat resistant and shock resistant and submersible and vibration resistant and watertight

## Mounting Bolt Circle Diameter:

3.156 inches

## Furnished Items And Quantity:

Mtg hdw 3

## Indicator Type:

Dial w/pointer

## Installation Design:

Panel

## Mounting Arrangement Style:

Three hole/stud bolt circle

#### Sensitivity Rating:

150.0 millivolts

## Dial Scale Marking Color:

Black single indicator single range

## Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

#### Unable To Decode:

Unable to decode or unable to decode

#### Meter Depth Behind Mounting Flange:

1.660 inches

## Meter Body Diameter Behind Mounting Flange:

2.800 inches

#### Movement Type:

Moving coil, permanent magnet

#### **Background Color:**

White single indicator single range

#### **Pointer Color:**

Black single indicator single range

# NSN 6625-00-668-7400

Ammeter - Page 2 of 2



## **Power Source:** External Mounting Facility Type And Quantity: 3 threaded stud Scale Graduation Type: Linear single indicator single range **Measurement Range:** +0.0/+1.5 milliamperes, dc single indicator single range **Mounting Stud Diameter:** 0.138 inches **Scale Selection Method:** Terminal **Features Provided:** Luminous scale marking and magnetic shield and zero adjuster **Movement Suspension Method:** Jewel pivot base **Circuit Attachment Method And Quantity:** 2 solder stud and 2 threaded stud **Special Features:** Ruggedized Material: Steel **Nuclear Hardness Critical Feature:** Nonhardened Style Designator: Round flush mtg **Test Data Document:** 81349-mil-m-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 81349-mil-m-10304/12 government specification **Specification Or Standard:** Mr36 type **Fsc Application Data:** Test set, elect. Equip. Shelf Life: N/a Unit Of Measure: ---**Demilitarization:**

No

Fiig:

A310a0