NSN 6625-00-668-7636

Voltmeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-668-7636

Dc	r Which Designed:
	nding Voltago In Volta
3000.0	nding Voltage In Volts:
Overall Length:	
2.850 inches	
Mounting Hole Dia	meter-
-	es and 0.157 inches
Scale Division Qua	
80 single indicator s	
Overall Diameter:	
3.510 inches	
Environmental Pro	tection.
	istant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and
water resistant	
Mounting Bolt Circ	le Diameter:
3.160 inches	
Furnished Items A	nd Quantity:
Nut 7; lockwasher {	
Indicator Type:	
Dial w/pointer	
Installation Design	:
Panel	
Mounting Arrange	ment Style:
Three hole/stud bolt	circle
Sensitivity Rating:	
150.0 millivolts	
Dial Scale Marking	Color:
Black single indicate	or single range
Accuracy In Perce	nt:
-2.0 to 2.0 at full sca	ale single indicator single range
Unable To Decode	:
Unable to decode o	r unable to decode
Meter Depth Behin	d Mounting Flange:
1.660 inches	
Meter Body Diame	ter Behind Mounting Flange:
2.800 inches	
Movement Type:	
Moving coil, perma	nent magnet
Background Color	:
White single indicate	or single range
Pointer Color:	

Black single indicator single range

NSN 6625-00-668-7636

Voltmeter - Page 2 of 2



Power Source: External	
	Type And Quantity:
3 screw and 3 until	
Scale Graduation	
Linear single indic	
Measurement Ra	-
	dc single indicator single range
Scale Selection N	ethod:
Terminal	
Features Provide	
Magnetic shield ar	-
Movement Suspe	nsion Method:
Jewel pivot base	
	nt Method And Quantity:
2 solder lug and 2	
Special Features	
Ruggedized	
Special Markings	
On back, sealed d	o not open
Material:	
Steel	
Nuclear Hardnes	Critical Feature:
Nonhardened	
Surface Treatmer	t:
Chromate	
Style Designator:	
Round flush mtg	
Test Data Docum	ent:
81349-mil-m-1030	4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes of	ommercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and	performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Dat	a:
81349-mil-m-1030	1/11 government specification
Fsc Application [ata:
Test set, elect. Eq	lip.
Shelf Life:	
N/a	
Unit Of Measure:	

Demilitarization:

Yes - demil/mli

Fiig:

A310a0