

View Online at <https://aerobasegroup.com/nsn/6625-00-668-7683>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

3.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.859 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.859 inches

Overall Height:

2.343 inches

Overall Width:

2.343 inches

Mounting Hole Diameter:

0.140 inches

Scale Division Quantity:

30 single indicator all ranges

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Furnished Items And Quantity:

Nut 4; flat washer 4; shunt 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

30.0 millivolts

Dial Scale Marking Color:

Yellow single indicator all ranges

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.875 inches

Meter Body Diameter Behind Mounting Flange:

2.156 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

Black single indicator all ranges

Pointer Color:

White and yellow single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

3 clip and 3 unthreaded hole

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+0.0 to 30.0 volts single indicator 2nd range

Scale Selection Method:

Switch

Features Provided:

External shunting and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

4 threaded stud

Special Features:

Ruggedized

Special Markings:

On front, amps; +; amps; volts

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Special Test Features:

Complies with mil-m-10304

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0